

PUBLICATION NUMBER : 59108970
 PUBLICATION DATE : 23-06-84



APPLICATION DATE : 13-12-82
 APPLICATION NUMBER : 57219073

APPLICANT : NIPPON STEEL CORP;

INVENTOR : TAKATO HIDEO;

INT.CL. : G01R 33/12 G01N 27/72

TITLE : MEASURING OF MAGNETIC PROPERTY OF STEEL MATERIAL



ABSTRACT : PURPOSE: To achieve simultaneous measurement of magnetic characteristic value in a contactless manner and online by determining characteristic of variations in the penetration of magnetic flux with respect to changes in an exciting current of an electromagnet employing a magnetic detector provided on one side of a steel material to be measured while the electromagnet on the other side thereof sandwiching it to measure a magnetic characteristic value of the steel material from the resultant characteristic curve.

CONSTITUTION: Magnetic flux 5 generated from a magnetic core 2 comprising magnetic flux 5₁ passing through a steel material 1 and magnetic flux 5₂ penetrating through the back thereof. An apparatus 7 receives the current proportional output E₁ of an exciting power source 4 and the output E₂ of a magnetic detector 6 and computes the magnetic characteristic of the steel material 1 being measured from a characteristic curve representing a relationship of both the outputs. The characteristic curve between the exciting current proportional output E₁ and the output E₂ of the magnetic detector varies in the sequence 0' → 2' → 3' → 4' → 5' → 2' as shown by the arrow, where the penetrating magnetic flux 5₂ decreases as the magnetic flux 5₁ passing through the steel material 1 being measured while it increases as the magnetic flux 5₁ decreases. Since the magnetic flux 5₁ in the steel material being measured is proportional to a magnetization factor thereof, the curve (E₁-E₂) is determined by the magnetization characteristic of the steel material to be measured, dimensional distances l₁ and l₂ thereof and the magnetization characteristic of a magnetic core 2.

COPYRIGHT: (C)1984,JPO&Japio